
TEGOLUX 2A033

Prodotto | Product | Produit | Produkt | Producto | Produkt

Lastra grecata in policarbonato compatto compatibile con **GRECA 76/18**
Corrugated polycarbonate solid sheet compatible with **GRECA 76/18**
Plaque ondulée en polycarbonate massif compatible avec **GRECA 76/18**
Wellplatten (Massiv) aus Polycarbonat, kompatibel mit **GRECA 76/18**
Placa grecada de policarbonato compacto compatible con **GRECA 76/18**
Placa Falista płyta z litego poliwęglanu kompatybilna z **GRECA 76/18**



Caratteristiche di produzione | Production features | Caractéristiques de production | Produktionseigenschaften | Caracteristicas productivas | Cechy produkcyjne

Production Features	Unit	Value
Spessore | Thickness | Épaisseur | Stärke | Espesor | Grubość	mm	0,8
Lunghezza massima consigliata | Maximum recommended length | Longueur maximale recommandée | Maximale empfohlene Länge | Longitud maxima recomendada | Maksymalna zalecana długość	mm	5.000
Larghezza totale | Total width | Largeur totale | Breite | Ancho total | Maksymalna zalecana szerokość	mm	1.040
Larghezza utile | Cover width | Largeur utile | Nutzbreite | Ancho útil | Szerokość krycia	mm	988
Altezza greca | Corrugation depth | Hauteur d'onde | Profilhöhe | Alto de greca | Głębokość fali	mm	18
Passo greca | Corrugation pitch | Largeur d'onde | Profilabstand | Ancho de greca | Rozstaw fali	mm	76
Raggio minimo di curvatura a freddo | Minimum cold bending radius | Rayon minimum de cintrage à froid | Mindestkaltbiegeradius | Radio mínimo de curvatura en frio | Minimalny promień gięcia na zimno	mm	10.000
Protezione UV | UV protection | Protection UV | UV Beschichtung | Protección UV | Ochrona UV		Protezione su un lato | Protected on one side | Protection sur un seul côté | Einseitig UV-beschichtet | Protección a una cara | Protección a una cara | Chroniona jednostronnie
Applicazione | Application | Application | Anwendung | Aplicaciones | Zastosowanie		Copertura continua | Continuous roofing | Couverture continue | Überdachungen bedachung | Cubierta continua | Pokrycia dachowe ciągłe
		Lucernario | Skylight | Lanterneau | Oberlicht | Lucernario | Świetliki
		Facciata | Facade | Bardage | Fassade | Fachada | Fachada | Felewacje
Pendenza minima | Minimum slope | Pente minimale | Mindestdachneigung | Pendiente mínima | Minimalny spadek		Copertura continua 7% | Continuous roofing 7% | Couverture continue 7% | Überdachungen bedachung 7% | Cubierta continua 7% | Pokrycia dachowe ciągłe 7%
		Lucernario 5% | Skylight 5% | Lanterneau 5% | Oberlicht 5% | Lucernario 5% | Świetliki 5%
Conformità normativa | Regulatory compliance | Conformité réglementaire | Einhaltung gesetzlicher Vorschriften | Cumplimiento normativo | Zgodność z normami		CE EN 1013:2012+A1:2014 Reg. (EU) 305/2011 (CPR) [1]

Proprietà generali | General Properties | Propriétés generales | Allgemeine Eigenschaften | Propriedades generales | Właściwości ogólne

Properties	Symbol	Method	Unit	Value
Trasmittanza termica | Thermal transmittance | Transmission thermique | Wärmedurchgang | Transmitancia térmica | Przenikalność cieplna	U_{ver}	EN ISO 10077-2	W/m²·K	5,7
	U_{hor}	EN ISO 10077-2	W/m²·K	6,9
Isolamento acustico | Sound insulation | Isolation acoustique | Schalldämmung | Aislamiento acústico | Izolacja akustyczna	R_w (C; C_{tr})	EN ISO 717-1	dB	-
Reazione al fuoco | Reaction to fire | Réaction au feu | Brandverhalten | Reacción al fuego | Reakcja na ogień		EN 13501-1	Class	B – s1, d0

[1] DOP disponibile | DOP available | DOP disponible | DOP unter: | DOP disponible | DOP dostępne na @https://www.gallina.it

DISCLAIMER - All the information contained in this data-sheet are reliable and given in good faith, but no binding for dott.gallina srl, in fact the company assumes no obligations for this information that can be subject of change without notice. Customer is responsable for respecting the correct installation laws and the chemical compatibility recommended by the producer and described in 'Use and Maintenance'/'Chemical Resistence' document that should be consulted on www.gallina.it

For more information or for checking the up-dated values please contact your local sales referent. Moreover the Techinal Department provide a customized support taking in charge the requests sent to info@gallina.it


© dott.gallina srl 2016
MEMBER of EPSE

Resistenza all'urto di un corpo duro di piccole dimensioni | Small hard body impact resistance | Résistance au choc d'un corps dur de faibles dimensions | Geringe Widerstandsfähigkeit bei harten Stößen | Resistencia al impacto de un cuerpo duro con pequeñas dimensiones | Odporność na uderzenie twardym ciałem		EN ISO 6603-1		Conforme | Pass | Conforme | Bestanden | Cumple
Potere calorifico inferiore | Lower heating value | Pouvoir calorifique inférieur | Brennwert | Poder calorífico inferior | Wartość opałowa netto	***LHV***	EN 16153	MJ/kg	29,8
Dilatazione termica lineare | Linear termal expansion | Dilatation thermique linéaire | Wärmedehnungskoeffizient | Dilatación térmica lineal | Liniowa rozszerzalność cieplna	α_L	EN 1013	mm/m·K	0,065
			K^{-1}	65×10^{-6}

Proprietà generali | General Properties | Propriétés generales | Allgemeine Eigenschaften | Propriedades generales

Properties	Symbol	Method	Unit	Value
Permeabilità al vapore acqueo | Water vapour permeability | Permeabilité à la vapeur d'eau | Wasserdampfdurchlässigkeit | Permeabilidad al vapor de agua | Przepuszczalność pary wodnej	δ	EN 1013	mg/m·h·Pa	$3,8 \times 10^{-5}$
Temperatura di rammollimento Vicat | Vicat softening point | Point de ramollissement Vicat | Vicat-Erweichungstemperatur | Punto de reblandamiento Vicat | Punkt mięknięcia Vicata		ISO 306 (B 50)	°C	146 - 151
Temperatura di impiego | Operating temperature | Température d'exploitation | Gebrauchstemperatur | Temperatura de uso | Zakres temperatury pracy			°C	-40 / +120
Garanzia | Warranty | Garantie | Garantie | Garantía | Gwarancja			Years	10
Trasmissione luminosa | Light Transmission | Transmission lumineuse | Lichtdurchlässigkeit | Transmisión luminosa | Przepuszczalność światła [2]	τ_v	EN 410 / EN 14500	%	≥ 90
		EN 13468-1	%	≥ 90

Resistenza al carico | Load resistance | Résistence à la charge | Belastungswerte | Resistencia a la carga | Odporność na obciążenie



[2] Cristallo | Clear | Cristal | Farblos | Cristal | Kryształ

DISCLAIMER - All the information contained in this data-sheet are reliable and given in good faith, but no binding for dott.gallina srl, in fact the company assumes no obligations for this information that can be subject of change without notice. Customer is responsable for respecting the correct installation laws and the chemical compatibility recommended by the producer and described in 'Use and Maintenance'/'Chemical Resistence' document that should be consulted on www.gallina.it

For more information or for checking the up-dated values please contact your local sales referent. Moreover the Techinal Department provide a customized support taking in charge the requests sent to info@gallina.it

© dott.gallina srl 2016
MEMBER of EPSE